Creating a Monitoring Zone with Child Devices

Last Modified on 10/06/2022 4:15 am EDT

Creating a Monitoring Zone with Child Devices

Procedure Steps

From System Administration, complete the following steps:

- 1. From the *Monitoring* menu, select *Monitor Zones*.
- 2. Select the Access Panel that is the Parent to the desired Child Device.
- 3. Change the Include All Child Devices drop-down to Specify Child Devices Individually.

ielect:		0.9	Name:				
Access Panels	٠	Default	t Map:		•		
Device	Segment		Device	Event Routing Group	Children	Parent Device	Sammant
2220	Default Segment		2220	None (All Events Always)		Parent Device	Default Segment
Specify Child Dev		Assign->					
Event Routing (
None (All Ev	ents Always)						

- 4. Click [Assign].
- 5. Change the **Select** drop-down to the type of Child Device that needs to be added to the Monitoring Zone, such as Alarm Panels.
- 6. The Child Devices are now displayed in the list, making them available for assignment to the Monitoring Zone. In this case, the Child Devices include the Alarm Panels configured in the system.

ielect. Alam Panela 🔹 👻				Name:				
Device	Parent Device	Segment	Default				2	
1100		the second se		Device	Event Routing Group	Children	Parent Device	Segment
1200	2220 2220	Default Segmer Default Segmer		2220	None (All Events Always)	Specify		Default Segment
		[Assign->					
*			<-Remove					
Specify Child Devi	ces individually	•						
Event Routing (Group							
None (All Ev								

Applies To

OnGuard (All versions)

Additional Information

Note: To add Children for other Access Panels, add them by following the above steps.