

# How to Disable the IdvmService.svclog File?

Last Modified on 10/06/2022 4:18 am EDT

How do you Disable the IdvmService.svclog File?

## Procedure Steps

1. Open the Web.config file which is typically located at C:\inetpub\wwwroot\LnI.OC.Services\IdvmWebHost.
2. Comment out a few sections of code using <! at the beginning of the line and a > at the end of the line of code.
3. You will need comment out the following sections of code:

3a: <add switchValue="Warning, ActivityTracing" name="System.ServiceModel">  
    <listeners>  
        <add name="WCF Service Model File Listener"/>  
    </listeners>  
</add>

3b: <add switchValue="All" name="System.ServiceModel.MessageLogging">  
    <listeners>  
        <add name="WCF Service Model File Listener"/>  
    </listeners>  
</add>

An example of this is:

```
<! This entry will enable WCF activity logging >  
<!  
<add switchValue="Warning, ActivityTracing" name="System.ServiceModel">  
    <listeners>  
        <add name="WCF Service Model File Listener"/>  
    </listeners>  
</add>  
>  
<! This entry will enable WCF message logging >  
<!  
<add switchValue="All" name="System.ServiceModel.MessageLogging">  
    <listeners>  
        <add name="WCF Service Model File Listener"/>  
    </listeners>  
</add>  
>
```

## Applies To

Browser-Based Applications; OnGuard (All versions)

## Additional Information

---