How to configure Directory Security for OnGuard ClickOnce Web sites in Internet Information Services

Last Modified on 10/06/2022 4:19 am EDT

How to configure directory security for OnGuard ClickOnce Web sites in Internet Information Services

Procedure Steps

1) From the Start menu, select Run. To launch IIS Manager, type inetmgr in the **Open** field, then click [OK].

For Windows XP or Windows Server 2003, follow steps 2-8 below.

2) Under the local computer entry, expand **Web Sites**.

3) Right-click on either the KioskClickOnce or FrontDeskClickOnce virtual directory, then select **Properties**.

4) Select the Directory Security tab, then click [Edit] in the **Anonymous access and authentication control** section.

5) Ensure that Anonymous access and Integrated Windows authentication are selected.

- 6) Click [OK] to save the change, and then [OK] again to exit Web Site Properties.
- 7) Repeat steps 2-6 if you want to change another virtual directory.
- 8) Restart IIS, then restart the LS Application Server service.

For Windows Vista or Windows Server 2008, follow steps 9-11 below.

9) In the IIS Manager window, for either the KioskClickOnce or FrontDeskClickOnce virtual directory, double-click **Authentication**.

10) Ensure that **Anonymous Authentication** and **Integrated Windows authentication** are both set to Enabled.

11) Restart the IIS services, then restart the LS Application Server service if any changes were made.

Applies To

OnGuard 2009 (6.3.249) or later Windows XP Windows Vista Windows Server 2003 Windows Server 2008

Additional Information

None